

Display:

Type:	DLP Lamp
Resolution:	3840 x 2160
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	0.75m~9.76m (100"@2.50m)
Throw Ratio:	1.13-1.47
Keystone:	Vertical (+/- 40º) / Horizontal (+/- 40º)
Lens:	1.3x optical zoom
Light Source (watt):	240
Light Source Life, Normal (hours):	4000
Light Source Life, Dynamic Eco-Mode (hours):	20000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	12,000:1
Aspect Ratio:	16:9

Video Signal:

Frequency Horizontal:	15K-129KHz
Frequency Vertical:	23-240Hz

Compatibility:

PC Resolution (max):	3840 x 2160
Mac® Resolution (max):	3840 x 2160

Connector:

USB 2.0 Type A(1), USB 3.1 Type C(1), Ethernet LAN (RJ45)(1), 3.5mm 12V Trigger(1), 3.5mm Audio Out(1), Control (RS232)(1), HDMI 2.0 (with HDCP 2.2)(2)

Audio:

Internal Speakers:	10W (x1)
--------------------	----------

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	310W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104º F (0 - 40º C)
Humidity (non-condensing):	0-90%

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	6.2
Gross (lbs):	8.8

Weight (metric):

Net (kg):	2.8
Gross (kg):	4.0

Dimensions (imperial) (WxHxD):

Packaging (in.):	16.3 x 6.6 x 11.7
Physical (in.):	12.2 x 8.7 x 4.3

Dimensions (metric) (WxHxD):

Packaging (mm):	415.0 x 168.0 x 297.0
Physical (mm):	312.0 x 222.0 x 108.0

General:

Regulations:	FCC, cTUVus, ROHS
PACKAGE CONTENTS:	Projector, power cable, remote control, USB-C Cable, Quick Start Guide
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
UPC:	766907008951

Accessories:

HB10B, PJ-CASE-008, PJ-SCW-1001W, PJ-WMK-006, VCB10, VSR100
